



SPECIFICATION		
Sensor Type	2/3"	
resolution	2M	
Focal Length	50±5% mm	
FNo.	F1.8~C	
Optical FOV(D)	12.5° ±2°	
Optical FOV(H)	9.1° ±2°	
Optical FOV(V)	7.5° ±2°	
TV Distortion	-0.22%	
Focusing range	0.5m~∞	
Mechanical BFL(E)	17.526mm	
Control	Focus	Mannual
	Iris	Mannual
Mount	C	
filter size	M30.5xP0.5	
Suitable temperature	-10℃~+50℃	

Feature:

- extra large aperture, starligh level imaging lense
- Multi-coated, higher transmittance and less stray light
- HRI and LD glass, high resolution imaging optics
- glass+metal design, broad range of operating temperature
- used for 2/3" megapixel camera gun

③					MATERIAL			洛阳拜波赫光电科技有限公司	
②					TREAT			PART NO.	BBH03006-2M5018
①					NAME	DATE			
①	19.12.04				ZKW	16.10.16		PART NAME	REV.
REV.	DATE	DESCRIPTION	REVISED	APPR.	DRAWN				
				3RD ANGLE PROJN	CHECKED			SCALE	2:1
					AUDI			SHEET 1 OF 1	
					APPR.				