



SPECIFICATION		
Sensor Type	2/3"	
resolution	2M	
Focal Length	35±5% mm	
FNo.	F1.4~C	
Optical FOV(D)	17.7° ±2°	
Optical FOV(H)	14.2° ±2°	
Optical FOV(V)	10.7° ±2°	
TV Distortion	-0.33%	
Focusing range	0.3m~∞	
Mechanical BFL(E)	17.526mm	
Control	Focus	Mannual
	Iris	Mannual
Mount	C	
filter size	M30.5xP0.5	
Suitable temperature	-10℃~+50℃	

Feature:

- extra large aperture, starligh level imaging lense
- Multi-coated, higher transmittance and less stray light
- HRI and LD glass, high resolution imaging optics
- glass+metal design, broad range of operating temperature
- used for 2/3" megapixel camera gun

③					MATERIAL			洛阳拜波赫光电科技有限公司		
②					TREAT			PART NO.	BBH03007-2M3514	
①						NAME	DATE			
①	19.12.04					ZKW	16.12.10			
REV.	DATE	DESCRIPTION	REVISED	APPR.	DRAWN			PART NAME	REV.	
					CHECKED					1
					AUDI					
					APPR.			SCALE	2:1 SHEET 1 OF 1	

3RD ANGLE
PROJN