



SPECIFICATION		
Sensor Type	2/3"	
resolution	2M	
Focal Length	12±5% mm	
FNo.	F1.4~22	
Optical FOV(D)	49.1°±2°	
Optical FOV(H)	40.1°±2°	
Optical FOV(V)	30.5°±2°	
TV Distortion	-1.70%	
Focusing range	0.15m~∞	
Mechanical BFL(E)	17.526mm	
Control	Focus	Mannual
	Iris	Mannual
Mount	C	
filter size	M30.5xP0.5	
Suitable temperature	-10℃~+50℃	

Feature:

- extra large aperture, starligh level imaging lense
- Multi-coated, higher transmittance and less stray light
- HRI and LD glass, high resolution imaging optics
- glass+metal design, broad range of operating temperature
- used for 2/3" megapixel camera gun

③					MATERIAL			洛阳拜波赫光电科技有限公司	
②					TREAT			PART NO.	BBH03010-2M1214
①					DRAWN	NAME	DATE		
①	19.12.04				ZKW		17.06.26		
REV.	DATE	DESCRIPTION	REVISED	APPR.	CHECKED			PART NAME	REV.
					AUDI				1
					APPR.			SCALE	2:1 SHEET 1 OF 1

3RD ANGLE  
PROJN