



SPECIFICATION		
Sensor Type	1"	
resolution	5M	
Focal Length	$16 \pm 5\%$ mm	
FNo.	F1.6~22	
Optical FOV(D)	$55^\circ \pm 2^\circ$	
Optical FOV(H)	$45^\circ \pm 2^\circ$	
Optical FOV(V)	$34^\circ \pm 2^\circ$	
TV Distortion	-3.90%	
Focusing range	1.0m~ ∞	
Mechanical BFL(E)	17.526mm	
Control	Focus	Manual
	Iris	Manual
Mount	C	
filter size	M37.5xP0.5	
Suitable temperature	-10℃~+50℃	

Feature:

- extra large aperture, starligh level imaging lense
- Multi-coated, higher transmittance and less stray light
- HRI and LD glass, high resolution imaging optics
- glass+metal desigh, broad range of operating temperature
- used for 1" megapixel camera gun

					MATERIAL		洛阳拜波赫光电科技有限公司	
					TREAT		PART NO.	BBH03013-5M1616
					NAME	DATE		
	19.12.04				ZKW	17.12.21	PART NAME	REV. 1
REV.	DATE	DESCRIPTION	REVISED	APPR.	CHECKED			
					AUDI		SHEET 1 OF 1	
					APPR.			

3RD ANGLE
PROJN