



SPECIFICATION		
Sensor Type	4/3"	
resolution	10M	
Focal Length	25±5% mm	
FNo.	F2.0~22	
Optical FOV(D)	49.7° ±2°	
Optical FOV(H)	40.6° ±2°	
Optical FOV(V)	31° ±2°	
TV Distortion	-0.70%	
Focusing range	0.15m~∞	
Mechanical BFL(E)	17.526mm	
Control	Focus	Manual
	Iris	Manual
Mount	C	
filter size	M46xP0.75	
Suitable temperature	-10°C~+50°C	

Feature:

Large aperture, starlight level imaging lense
 multi-coated, higher transmittance and less stray light
 HRI and 1D glass, high resolution imaging optics
 glass + metal design, broad range of operating temperature
 used for 4/3" megapixel camera gun

③					MATERIAL			洛阳拜波赫光电科技有限公司	
②					TREAT				
①						NAME	DATE	PART NO.	BBH03020-10M2520
①	19.12.04					ZKW	19.07.06		
REV.	DATE	DESCRIPTION	REVISED	APPR.	DRAWN			PART NAME	REV.
					CHECKED				
				3RD ANGLE PROJN ⊕	AUDI			SCALE	2:1
					APPR.				SHEET 1 OF 1